



# **Arrangements Round Large**

F0408030 - Black

Designed by Michael Anastassiades

 $Diffuse\ light suspended\ lighting\ device.\ Body\ in\ extruded,\ curved\ NC-machined\ and\ black\ powder-coated$ aluminium, diffuser in platinum optical silicone.

Each component can be connected to the power pack by means of an electrical and mechanical connection system designed for customisable product set-up.

Roses available with two powers: lamp with power under 70W and lamp with power under 190W. Class III roses also available for installations with remote power supply: "surface" version for installations on cement, "recessed" version for plasterboard ceilings.


The electronics integrated in the rose enables use of dimming systems: push, 1-10, potentiometer, DALI. In the absence of these systems, the light flow can be set with the push system included in the rose. Cable length 2.4m

### Main specifications

Suspension	Lamp holder	LED Module
Indoor dry	Dimmable	Yes
location	Autoprotected Lamp	No
LED	Number of heads	1
Replaceable (LED only) light source by a professional	Source Power (W)	54
LED Module 2751		
	Indoor dry location LED Replaceable (LED only) light source by a professional LED Module	Indoor dry location LED Replaceable (LED only) light source by a professional LED Module  Dimmable Autoprotected Lamp Number of heads Source Power (W)

### Optical

Lighting Type	Indirect, Direc
Lighting distribution	Symmetric
CCT (K)	2700
Cold Beam Lighting	No
Extreme Cut off	No



#### Electrical

Insulation class Frequency (Hz) Main Voltage (Vac) Driver	111 50/60 48 Remote	Batteries Inside Dimming Interface	No Remote Dimmable (Dimmer Not
Dimmable	Yes	Cord length (mm) Charging Min Time	Included) 2500 No


## **Physical**

Colour	Black
Net weight (kg)	1.2
Gross weight (kg)	2.65
IP	20
IP external	20



# **Arrangements Round Large**







F0415030



**Arrangements Recessed** Rose F0418030