





Designed by Rodolfo Dordoni

 $Wall\ lamp\ providing\ direct/indirect\ light.\ Pressure\ die-cast\ Zamak\ alloy\ structure,\ matte\ gray,\ shiny\ white\ or\ alloy\ structure,\ matte\ gray,\ shiny\ structure,\ matte\ gray,\ shiny\ shiny\ structure,\ shiny\ shi$ chrome plated finish. Molded steel, galvanized white wall attachment containing the wall attachment system as well as the electrical devices.







145 mm		
	197 mm	99 mm



Main specifications

Mounting	Wall	Lamp holder	LED Module
Environment	Indoor dry	Autoprotected Lamp	No
	location	Number of heads	2
Light source type	LED	Source Power (W)	21.5
Light source replaceable	Replaceable	System Flux (Im)	1744

source by a professional LED Module LED type

Optical

Lighting Type	Indirect, Direct
Lighting distribution	Asym m etric
CCT (K)	2700
CRI>	90
Cold Beam Lighting	No
Extreme Cut off	No

Electrical

Insulation class	1	Batteries Inside	No
Frequency (Hz)	50/60	Power supply replaceable	Replaceable
Main Voltage (Vac)	220-240		control gear by
Driver	Integrated		a professional
Dimmable type	Dimmable 1-	Charging Min Time	No
	10\/		

Physical

Colour	Grey
Net weight (kg)	1.7
Gross weight (kg)	3.75
IP	20
IP external	20